

PSEN 1.1b-22/PSEN 1.1-20 /8mm/10m/ix1/1u

504229



Magnetic safety switch 2 N/O, square design. Height design 13 mm IP6K9K, operating distance 8 mm, for applications with PSEN ix1 PU = 1 piece with actuator, with 10 m cable (PUR).

Technical details

| | |
|-----------------------------|----------------------------|
| Certifications: | CE;cULus Listed;TÜV;ECOLAB |
| Sensor principle: | magnetic |
| Number of N/O: | 2 |
| Connection type: | 10m Kabel |
| Switching voltage: | 24 V |
| Type of switching voltage: | DC |
| Assured switching distance: | 8.0 mm |
| Assured release distance: | 26.0 mm |
| Protection type, housing: | IP69K |
| Status indicator: | Without LED |
| Design: | square |
| Width dimension: | 26.0 mm |
| Height dimension: | 36.0 mm |
| Depth dimension: | 13.0 mm |
| Gross weight: | 370 g |
| Net weight: | 357 g |
| Ambient temperature: | -10 - 70 °C |

Accessories



535120

PSEN ix1 Interface for 4 PSEN 1

Optional accessories



380308

PSS67 M12 connector, straight, male, 5pole



380310

PSS67 M12 connector, angled, male, 5pole



532110

PSEN Winkel / bracket



534310

PSEN Distanzplatte / spacer (10 pcs.)



534320

PSEN reverse spacer



535120

PSEN ix1 Interface for 4 PSEN 1



540310

PSEN screw M4x16 10pcs