

PSEN 1.1b-25/PSEN1.1-20/8mm/10m/EX/1unit

504251



Magnetic safety switch 2 N/O, square design. Height design 13 mm IP6K9K, operating distance 8 mm, for applications with PSEN ix1 PU = 1 piece with actuator, with 10 m cable (PUR), ATEX approval.

## Technical details

Certifications:	CE;cULus Listed;ATEX;TÜV;ECOLAB;electrosuisse
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	10m Kabel
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP69K
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	36.0 mm
Depth dimension:	13.0 mm
Gross weight:	370 g
Net weight:	357 g
Ambient temperature:	-10 - 55 °C

## Accessories



535120

PSEN ix1 Interface for 4 PSEN 1

## Optional accessories



532110

PSEN Winkel / bracket



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m

---



533141

PSEN Kabel Gerade/cable straightplug 30m

---



534310

PSEN Distanzplatte / spacer (10 pcs.)

---



534320

PSEN reverse spacer

---



535120

PSEN ix1 Interface for 4 PSEN 1

---



540310

PSEN screw M4x16 10pcs

---