

PSEN ma1.3p-22/PSEN ma1.3-12/12mm/ix1/1u

506237



Magnetic safety switch 3 N/O, M8 male connector, round M12 design IP67, operating distance 12 mm, for applications with PSEN ix1, PU = 1 piece with cuboid actuator.

Technical details

Certifications:	CE;cULus Listed;TÜV;ECOLAB
Sensor principle:	magnetic
Number of N/O:	3
Connection type:	M8, 8pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	12.0 mm
Assured release distance:	25.0 mm
Protection type, housing:	IP65
Status indicator:	With LED
Design:	Round
Width dimension:	12.0 mm
Height dimension:	11.0 mm
Depth dimension:	59.1 mm
Gross weight:	65 g
Net weight:	30 g
Ambient temperature:	-25 - 70 °C

Accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m



535120

PSEN ix1 Interface for 4 PSEN 1

Optional accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m



533155

PSEN cable M8-8sf M8-sm, 0.5m



533156

PSEN cable M8-8sf M8-8sm, 1m




533157

PSEN cable M8-8sf M8-8sm, 2m



535120

PSEN ix1 Interface for 4 PSEN 1



540329

PSEN converter M8-8sf -- M12-8sm
