

PSEN opII4F-s-14-045

632082

Safety light curtain, type 4, PL e, finger protection (resolution 14 mm)
Protected field height 450 mm, supply voltage 24 V, without dead zone
Connector: M12, sender: 5-pole, receiver 5-pole Connection cable not supplied with the unit.



Technical details

Certifications:	CE;cULus Listed;TÜV;KOSHA
Sensor principle:	Infrared
Number of beams:	48
Height of protected field:	450 mm
Operating range (m):	0,2 - 8,0
Reaction time:	8.40 ms
Number of OSSD outputs:	2
Muting:	No
Blanking:	No
Cascading:	No
Protection type, housing:	IP65
Supply voltage (V):	24,0
Supply voltage type:	DC
Resolution of safety device:	14 mm
Application in accordance with:	EN 61496-1;EN 61496-2
Width dimension:	35.0 mm
Height dimension:	454.0 mm
Depth dimension:	40.0 mm
Gross weight:	1658 g
Net weight:	1438 g

Ambient temperature:

-10 - 60 °C

Accessories



632018

PSEN opII Testpiece F 14 mm

Optional accessories



380208

PSS67 Cable M12sf M12sm, 3m



380209

PSS67 Cable M12sf M12sm, 5m



380210

PSS67 Cable M12sf M12sm, 10m



380211

PSS67 Cable M12sf M12sm, 30m



380212

PSS67 Cable M12af M12am, 3m



380213

PSS67 Cable M12af M12am, 5m



380214

PSS67 Cable M12af M12am, 10m



380215

PSS67 Cable M12af M12am, 30m



630297

PSEN op cable axial M12 5-pole 30m



630310

PSEN op cable axial M12 5-pole 3m



630311

PSEN op cable axial M12 5-pole 5m



630312

PSEN op cable axial M12 5-pole 10m



630347

PSEN op cable angle M12 5-pole 3m



630348

PSEN op cable angle M12 5-pole 5m



630349

PSEN op cable angle M12 5-pole 10m



630350

PSEN op cable angle M12 5-pole 30m



380220

PSS67 cable M12-5sf, M12-5sm, 20m



630950

PSEN op Protective Column-060/1



630951

PSEN op Protective Column-090/1



630952

PSEN op Protective Column-120/1



630955

PSEN op Protective Base/1



630957

PSEN op Protective Bracket-6/1



630953

PSEN op Protective Column-165/1



630954

PSEN op Protective Column-190/1



630956

PSEN op Protective Bracket-4/1

	630912	PSEN op Lens Shield-045/1
	630298	PSEN cable M12-5sf 20m
	630365	PSEN op cable angle M12 5-pole 50m
	630364	PSEN op cable axial M12 5-pole 50m
	632015	PSEN opII Bracket Kit
	632014	PSEN opII Laserpointer
	632017	PSEN opII Adv Bracket Kit-3
	632016	PSEN opII Adv Bracket Kit-2