

PNOZ ml1p safe link 24VDC

773540



Configurable safety system PNOZmulti expansion module Safe connection, communication interface.

Technical details

| | |
|--|--------------------------------|
| Certifications: | CE;cULus Listed;BG;TÜV;CCC;KCC |
| Number of safe virtual inputs: | 32 |
| Number of safe virtual outputs: | 32 |
| Max. data transmission time: | 35 ms |
| Supply voltage (V): | 24,0 |
| Power consumption DC: | 5.0 W |
| Version for extreme environ. conditions: | Standard |
| Width dimension: | 22.5 mm |
| Height dimension: | 94.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 148 g |
| Net weight: | 129 g |
| Ambient temperature: | 0 - 60 °C |

Accessories



783400

PNOZmulti Set spring loaded terminals



793400

PNOZ mi1p/mi2p/mo1p screw terminals

Optional accessories



380000

SafetyNET p Cable per mtr



773890

PNOZ mli1p 5m



773891

PNOZ mli1p 10m screw



773892

PNOZ mli1p 50m



773893

PNOZ mli1p 5m

773894

PNOZ mli1p 10m



773895

PNOZ mli1p 50m



773896

PNOZ mli1p 1,5m spring



773897

PNOZ mli1p 1,5m screw



774639

KOP-XE



779110

PNOZmulti Bus-Terminator